



110410


PRIMA LED Ex 2/21 1.2ft PCc 2200/840 3F

8596328104107



- Degree of protection: IP66
- Ambient temperature: -25–55 °C
- Impact strength: IK10
- Life time: 50000 hours
- System efficacy: 140 lm/W
- Cable glands: M20X1,5, ATEX thread
- Protection class: I
- Power factor: 0,95
- Energy efficiency class of the light source: C

- Body: Grey PC (high mechanical resistance, UV stability, RAL 7035)
- Diffuser: Translucent PC (high mechanical resistance, UV stability)
- Reflector: Steel sheet, white (RAL 9003)
- Clips: Stainless steel + polyamide
- Sealing: Polyurethane (PUR), foam-filled base groove
- Connection: Screwless five-pole terminal block, 5-wire connecting cabling for feed-through installation (1.5 mm2 cross-section, 2.5 mm2 available on demand)
- Light fitting certified for environments with potentially explosive atmospheres created by gas, dust or flammable vapours, group II, category 3 (zone 2/21)
- For use in potentially explosive environments. For definition, see the assembly manual and certificate
- Optimal mounting height: 3 to 8 m
- ON/OFF electronic driver (AC, DC on demand)



Code	Type	Ta Max.: [°C]	Luminous flux of LED modules [lm]	Luminous flux of light fitting: [lm]	Power consumption: [W]	System efficacy: [lm/W]	Net weight: [kg]	A [mm]	D [mm]
110410	PRIMA LED Ex 2/21 1.2ft PCc 2200/840 3F	55	2360	2050	14,6	140	2,2	662	350

The values stated for power consumption and luminous flux are in a tolerance of ± 7.5 %

FEATURES




CERTIFICATION



DOWNLOAD





110410

PRIMA LED Ex 2/21 1.2ft PCc 2200/840 3F

8596328104107

